



1120

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence



CONFIGURATIONS



1120
Standard



1120NF
No Foam

DIMENSIONS

Interior (L x W x D)	7.29 x 4.78" x 3.33 (18.5 x 12.1 x 8.5 cm)
Exterior (L x W x D)	8.41 x 6.76" x 3.87 (21.4 x 17.2 x 9.8 cm)
Lid Depth	0.50" (1.3 cm)
Bottom Depth	2.56" (6.5 cm)
Total Depth	3.06" (7.8 cm)
Int Volume	0.07 ft³ (0.002 m³)

MATERIALS

Body	Polypropylene
Latch	Polypropylene
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

- Black
- Silver
- Orange
- Yellow
- Blue
- OD Green
- Desert Tan

WEIGHT

Weight With Foam	1.43 lbs (0.6 kg)
Weight Empty	1.34 lbs (0.6 kg)
Master Pack Weight	10.45 lbs (4.7 kg)

TEMPERATURE

Minimum Temperature	-40°
Maximum Temperature	210°

CERTIFICATIONS

IP67
Def Stan 81-41
STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid)	0.75" Convolute
Layer 2 (Base)	0.38" Pad
Layer 3 (Base)	2.12" Pick N Pluck

OTHER

Master Pack	6
Military	yes

ACCESSORIES



1121
3 pc. Replacement Foam Set



1123
Replacement O-ring



1120PF
Special Application Panel Frame



3/13 Veronica Street, Capalaba, Brisbane, Qld 4157
Tel: 07-3245 2699
Email: sales@qldcase.com.au
Web: www.qldcase.com.au