



# 1510

## Protector Carry-On Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Maximum airline carry on size\***
- Retractable extension handle
- **Strong polyurethane wheels with stainless steel bearings**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Stainless steel hardware and padlock protectors
- Personalized nameplate service available
- Lifetime Guarantee of Excellence
- **Watertight, crushproof, and dustproof**
- \* Check with your airline for exact measurement requirements.



### CONFIGURATIONS



**1510**  
Standard



**1514**  
With Padded Dividers



**1510NF**  
No Foam



**1510TP**  
With TrekPak Divider System

### DIMENSIONS

<b>Interior (L x W x D)</b>	19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm)
<b>Exterior (L x W x D)</b>	22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)
<b>Lid Depth</b>	1.79" (4.5 cm)
<b>Bottom Depth</b>	5.79" (14.7 cm)
<b>Total Depth</b>	7.58" (19.3 cm)
<b>Int Volume</b>	0.96 ft³ (0.027 m³)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

## COLOURS

■ Black

■ OD Green

■ Desert Tan

## WEIGHT

<b>Weight With Foam</b>	13.60 lbs (6.2 kg)
<b>Weight Empty</b>	11.99 lbs (5.4 kg)
<b>Buoyancy</b>	64.15 lbs (29.1 kg)
<b>Master Pack Weight</b>	32.43 lbs (14.7 kg)

## TEMPERATURE

<b>Minimum Temperature</b>	-40°
<b>Maximum Temperature</b>	210°

## CERTIFICATIONS

IP67  
Def Stan 81-41  
STANAG 4280

## FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	1.81" Convolute
<b>Layer 2 (Base)</b>	0.50" Pad
<b>Layer 3 (Base)</b>	2.63" Pick N Pluck
<b>Layer 4 (Base)</b>	2.63" Pick N Pluck

## OTHER

<b>Wheels</b>	2
<b>Extendable Handle</b>	yes
<b>Master Pack</b>	2
<b>Nameplate</b>	yes
<b>Reduced Area</b>	yes
<b>Military</b>	yes

---

## ACCESSORIES



**1511**  
4 pc. Replacement Foam Set



**1513**  
Replacement O-ring



**1515**  
Padded Divider Set



**1519**  
Lid Organizer



3/13 Veronica Street, Capalaba, Brisbane, Qld 4157  
Tel. 07-3245 2699  
Email: sales@qldcase.com.au  
Web: www.qldcase.com.au