

IS2117-1103

ISP Case

Shifting loose cargo can slow down your ops and threaten the mission with damaged freight. The new ISP Case from Pelican™ virtually eliminates load movement with a unique Inter-Stacking Pattern (ISP). The patent pending system is compatible across 6 different case sizes from 4 to 25 cubic feet of storage. Equipped with a silicone sponge O-ring and pressure release valves, the ISP Case is impervious to extreme weather and wet conditions.

The system is designed to maximize the volume of standard logistics platforms. Whether loading standard pallets, NATO pallets, JMIC containers, 463L pallets or sea containers, the ISP Case system will make the most efficient use of cargo space.

With its Inter-Stacking Pattern there is no question where the next case belongs. The disc pattern bottom mates with the wave pattern on the case below, literally falling and locking into place. Cross-stacking builds incredibly tight loads that can save time with strapping or netting.



CONFIGURATIONS



IS2117-1103 Standard



IS2117-1103-No-Foam No Foam

DIMENSIONS

21.00 x 17.00" x 14.00 (53.3 x 43.2 x 35.6 cm) Interior (L x W x D) Exterior (L x W x D) 24.00 x 20.00" x 16.00 (61 x 50.8 x 40.6 cm)

Lid Depth 3.00" (7.6 cm) **Bottom Depth** 11.00" (27.9 cm) **Total Depth** 14" (35.6 cm) Int Volume 2.89 ft3 (0.082 m3)

MATERIALS

Body RotoMolded Polyethylene Latch Steel (Nickel-black Plated)

O-Ring Silicone Sponge Stainless Steel **Pins** Pins (Alt) Aluminum **Purge Body** Aluminum

COLOURS

Black - 032 Fed Std

27040 34096

Olive Drab - Fed Std

Gray - 133 Fed Std 26270

Tan - 250 Fed Std 20372

Red - 130 Fed Std

WEIGHT

Weight With Foam 26.00 lbs (11.8 kg) Weight Empty 20.00 lbs (9.1 kg)

TEMPERATURE

-20° **Minimum Temperature**

21105

Maximum Temperature 140°

CERTIFICATIONS

MIL-STD-810F

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 04-18-18